STYRENIC THERMOPLASTIC ELASTOMER COMPOSITION

Patent number: JP2005089656

Publication date: 2005-04-07

Inventor: SHIN GAKILII

Applicant: MITSUBISHI CHEM CORP

Classification:

-international: C08L53/02; C08L23/00; C08L91/00; C08L53/00;

C08L23/00; C08L91/00; (IPC1-7); C08L53/02;

C08L23/00, C08L91/00

- european:

Application number: JP20030326759 20030918 Priority number(s): JP20030326759 20030918

Report a data error here

Abstract of JP2005089656

PROBLEM TO BE SOLVED. To provide a styrenic thermoplastic elastomer composition having good softness, extrusion moldability, surface gloss and scratch resistance. SOLUTION: The styrenic thermoplastic elastomer composition comprises (a) a block copolymer composed of a polymer block of a styrenic compound and a copolymer block of the styrenic compound with a conjugated diene and having >=50.000 and <=100.000 weight-average molecular weight and/or its hydrogenated block condumer, (b) an eleginic repi: (c) a settlem the high surface and the styrenic compound the styrenic compound the styrenic compound and a conjugated diene and having >=50.000 and <=100.000 weight-average molecular weight and/or its hydrogenated block condumer.

composed or a polymer alock of a syrenic compound and a copolymer block of the styrenic compound with a conjugated diene and having >=50,000 and <=100,000 weight-average molecular weight and/or lis hydrogenated block copolymer, (b) an olefinic resin, (c) a softener for hydrocarbon-based rubbers and (d) a block copolymer, composed of a polymer block of a styrenic compound and a polymer block of a conjugated diene and having >=50,000 and <=100,000 weight-average molecular weight, in which a ratio of 1,2-conjugate occupied in a unit derived from a conjugated diene is >=20% and <=50% and/or its hydrogenated block copolymer.

Data supplied from the esp@cenet database - Worldwide